



The security shield tool is permanently attached, 4/ 3/4" (120mm), and pivots in 90-degree increments.

These tools are ideal for hard to reach shielded F connectors F Connector fittings where a pre-set torque is required.

The **TWAFST-71622** is set at .22 in./lb (2.49 NM)

The **TWAFST-71630** is set at .30 in./lb (3.39 NM)

| SPECIFICATIONS | TWAFST-71622 | TWAFST-71630 |
|------------------------|-------------------------|-------------------------|
| HEAD TYPE | Swivel | Swivel |
| SIZE | 7/16" (11.11mm) Shield | 7/16" (11.11mm) Shield |
| TORQUE | 22 inch-lbs (2.49 N-m) | 30 inch-lbs (3.39 N-m) |
| SECURITY SHIELD LENGTH | 4 3/4" (120 mm) | 4 3/4" (120 mm) |
| MATERIAL | High Carbon Alloy Steel | High Carbon Alloy Steel |
| FINISH | Black Oxide | Black Oxide |
| HANDLE | Ergonomic Cushion Grip | Ergonomic Cushion Grip |
| COLOR | Blue Handle | Blue Handle |
| WEIGHT | 0.724 lbs | 0.724 lbs |
| UPC # | 811490016644 | 811490016651 |

