











## SPARC™ Blade Fiber Cleaver

Features an alloy steel blade that is fully automatic with self-activating scoring mechanism, auto blade rotation after each cleave, 2,500 cleaves per position, and a blade lifespan of over 60,000 cleaves. The SPARC Blade also features a built-in automatic fiber shard collector and a magnetic universal holder. It has been designed to cover a wide range of different cables, including 250µm & 900µm fiber cable, flat cable, ribbon fiber, and jumper cable. SPARC Blade also features a 90 degree lid for higher visibility and ease of use when working on fiber/maintenance.

## **SPECIFICATIONS**

Туре	Single and Ribbon Fiber
Cladding Diameter	125 µm
Cleaved Length	Single Fiber : 5mm - 24mm (Coating diameter: 250µm), 10mm - 20mm (Coating diameter> 250µm) Ribbon (Multi) Fiber: 10mm
Applicable Fiber Cable	Single Fiber: 160 μm to 900 μm, 2mm - 3mm and drop cable Ribbon (Multi) Fiber : 2 - 16 ribbon fiber
Cleaved Angle (Typical)	Single Fiber: 0.5°
Blade Life	Total 60,000 fiber cleaves (2,500 cleaves per each point, total 24 points)
Holder	Universal
Dimensions	4.07" x 4.19" x 2.17"(10.35 cm x 10.65 cm x 5.5 cm)
Weight	0.7 lb (319 g)